

High-Resolution Global Land Cover Maps and their Assessment

Qiongjie Xu ^{1,*}, Vasil Yordanov ¹, Lorenzo Bruzzone ² and Maria Antonia Brovelli ¹

¹ Department of Civil and Environmental Engineering (DICA), Politecnico di Milano, Milan, Italy; (qiongjie.xu, vasil.yordanov, maria.brovelli)@polimi.it

² Department of Information Engineering and Computer Science, University of Trento, Trento, Italy; lorenzo.bruzzone@unitn.it

* Correspondence: qiongjie.xu@polimi.it

Abstract: Global High-Resolution Land Cover Maps (GHRLCs), characterized by spatial resolutions higher than 30 meters per pixel, have become essential tools for environmental monitoring, urban planning, and climate modeling. Over the past two decades, new GHRLCs have emerged, offering increasingly detailed and timely representations of Earth's surface. This review provides an in-depth analysis of recent developments by examining the data sources, methodologies, and validation techniques utilized in more than 20 global binary and multi-class land cover products. The evolution of GHRLC production techniques is analyzed, starting from the use of singular source input data, such as multi-temporal remotely sensed optical imagery, to the integration of satellite radar and other geospatial data. The article highlights significant advances in data pre-processing and processing, showcasing a shift from classical methods to modern approaches, including machine learning (ML) and deep learning techniques (e.g., neural networks and transformers), and their direct application on powerful cloud-computing platforms. A comprehensive analysis of the temporal dimension of land cover products, where available, is conducted, highlighting a shift from decadal intervals to production intervals of less than a month. This review also addresses the ongoing challenge of land cover legend harmonization, a topic that remains crucial for ensuring consistency and comparability across datasets. Validation remains another critical aspect of GHRLC production. The methods used to assess map accuracy and reliability, including statistical techniques and visual inspections, are briefly discussed. The validation approaches adopted in recent studies are summarized, with an emphasis on their importance in maintaining data integrity and addressing emerging needs, such as the development of common validation datasets. Ultimately, this review aims to provide a comprehensive overview of the current state and future directions of GHRLC production and validation, highlighting the advancements that have shaped this rapidly evolving field.

Keywords: Land cover; High-resolution Land cover; Satellite remote sensing; Challenges and trends; Assessment

Citation: Xu, Q.; Yordanov, V.; Bruzzone, L.; Brovelli, M.B. High-Resolution Global Land Cover Maps and their Assessment Strategies. *ISPRS Int. J. Geo-Inf.* **2024**, *1*, 0. <https://doi.org/>

Received:

Revised:

Accepted:

Published:

Copyright: © 2025 by the authors. Submitted to *ISPRS Int. J. Geo-Inf.* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

0. Introduction

Land cover (LC) maps are essential tools for understanding human and natural processes within land systems. They are widely used among a variety of applications, including post-disaster recovery monitoring[1,2], urban planning[3], Sustainable Development Goals (SDGs) monitoring[4], and climate change research[5]. Given the escalating impacts of global climate change and human activities on ecosystems, there is an increasing demand for high-resolution, accurate, and up-to-date LC maps to effectively understand and respond to environmental land changes[6].

The rapid advancement of satellite remote sensing technology, cloud-based processing, and the extensive application of machine learning in remote sensing have enabled the rapid production of LC maps with high temporal and spatial resolutions. Landsat data has drawn significant attention due to its open-access policy, long-term temporal coverage, and 30-meter spatial resolution, leading to the development of numerous 30-meter resolution

global land cover (GLC) maps[7–15]. Since 2014, Sentinel satellites have been providing globally consistent optical and SAR data with a spatial resolution of 10–20 meters, driving the generation of 10-meter resolution GLC products[16], such as ESRI LULC[17], ESA WorldCover[18,19], and Google Dynamic World[20].

However, HRLC maps present varying classification results depending on the data sources and classification methods. Therefore, a comprehensive evaluation and comparison of these maps is crucial to ensuring their reliability across different applications. In recent years, several studies have explored the status, challenges, and trends in LC mapping from various perspectives. They focus on topics like Earth observation data[21,22], deep learning technologies[23–25], big data[26], or land-use and land-coverchange[27]. While some studies[28,29] provide general overviews of land cover mapping, there remains a lack of a systematic review that thoroughly compares and evaluates the data sources, key technologies and validation methodologies underlying these datasets.

Table 1. Overview of HRLC products used in this study.

Dataset name	Provider	Spatial resolution (m)	Temporal resolution	LC focus
GLC_FCS30D [14]	CAS	30	1985 - 2022	General
GWL_FCS30D [30]	CAS	30	2000 - 2022	Wetland
GISD30[11]	CAS	30	1985 - 2020	Built-Up
Dynamic World [20]	World Resources Institute Google	10	2015 - 2025	General
ESRI LULC [17]	Impact Observatory, Microsoft, and Esri	10	2017 - 2023	General
WorldCover [18] [19]	ESA	10	2020,2021	General
GLanCE v001 [10]	BU/EE/NASA ES/USGS EROS	30	2001 - 2019	General
GlobeLand30 [8]	NGCC	30	2000, 2010, 2019	General
FROM-GLC30 [31] [32] [7]	Tsinghua University	30	2010, 2015, 2017	General
FROM-GLC10 [31]	Tsinghua University	10	2017	General
World Settlement Footprint (WSF) [33] [34]	DLR	10	2015,2019	Built-Up
MapBiomass[35]	SEEG and Climate Observatory	30	1985 - 2023	General
GSW [9]	JRC	30	1984-2021	Water
GUF[36]	DLR	12	2011	Built-Up
GHS-BUILT-S R2023A [37]	JRC	10	2018	Built-Up
GHS BU S1 [38]	JRC	20	2011	Built-Up

Continued on next page

Table 1. (Continued) Overview of HRLC products used in this study.

Dataset name	Provider	Spatial resolution (m)	Temporal resolution	LC focus
GFC [39]	JRC	10	2020	Forest
FNF [40]	JAXA-EORC	25	2007 - 2010, 2015 - 2020	Forest
Tree canopy cover [41]	Hansen/UMD/ Google/USGS/NASA	30	2000	Forest

Given the importance of GHRLC maps for various applications, and the emergence of HRLC products over the past two decades, we aim to provide a comprehensive overview of the current status and future directions of GHRLC production and validation by examining the data sources, methods, and validation techniques used for more than 20 global binary or multi-class LC products with a spatial resolution of equal and smaller than 30 m. On the other hand, considering the critical role of the Amazon biome in the global climate, we also included HRLC specifically related to this region. A comprehensive list of all HRLC products utilized in this study is provided in Table 1. Except for Dynamic World, which provides near real-time updates of the land cover classification, all the HRLC products are with yearly temporal resolution.

1. Data inputs and technologies

1.1. Data sources

Diverse satellite imagery were utilized to generate GHRLCs, ranging from optical imagery to SAR data. Table 2 provides a summary of the satellite imagery and the GHRLCs that use them.

Table 2. Summary of Used Satellite Imagery and Related HRLCs from the Reviewed Literature

Data Type	Data Name	Used In
Optical Multispectral Imagery	Landsat	[13], [7–12,14,30,31,34,35,41]
	Sentinel-2	[17–20,31,33,37]
	HJ-1	[8]
Synthetic Aperture Radar (SAR) Data	Sentinel-1	[12,18,19,33,34,38]
	TanDEM-X (TDM)	[36]
	ALOS PALSAR	[40]

In the GHRLCs discussed in this paper, optical multispectral imagery from sources such as Landsat and Sentinel-2 serve as the primary data inputs due to its high spatial resolution, extensive temporal coverage, and free availability. Among these, Landsat is the most widely used, primarily because of its long time series and high spatial resolution (30 meters), making it especially valuable for generating long-term HRLC data. For instance, datasets such as GLC_FCS30D, GISD30, MapBiomass, and GSW have relied on Landsat imagery to generate HRLC maps spanning over 35 years. In contrast, although Sentinel-2, a high-resolution multispectral satellite constellation operated since 2015 by the European Space Agency, has somewhat more limited temporal coverage, it offers superior spatial resolution (10 meters) and a shorter revisit time (5 days)[42]. As a result, datasets such as FROM-GLC10, Dynamic World[20] and ESRI LULC[17], which are based on Sentinel-2 images, provide land cover information with higher spatial resolution.

While optical multispectral data are commonly used for LC mapping, they are constrained by cloud cover and varying lighting conditions. In contrast, SAR data from

missions such as ESA's Sentinel-1[43] and DLR's TanDEM-X offer all-weather capabilities, enabling them to penetrate cloud cover and, to some extent, vegetation, thereby providing valuable information about surface structure and moisture. For instance, datasets such as GUF, GHS BU S1, and FNF leverage radar backscattered information to enhance LC classification, demonstrating the valuable role of SAR data.

Although many GHRLCs rely on a single data source, some integrate multiple sources to improve coverage, accuracy, and reliability. For instance, GlobeLand30 combines images from Landsat TM/ETM+ and the China Environment and Disaster Satellite (HJ-1) to generate the 2020 GLC dataset, with the latter serving as a complementary source[8]. Multi-source data integration extends beyond combining different products from the same sensor type; it also involves fusing data from distinct sensor types. For example, WSF incorporates temporal statistics and texture features derived from Sentinel-1 and spectral indices from Landsat imagery to effectively characterize human settlements[34]. WorldCover dataset integrates Sentinel-1 and Sentinel-2 data[18,19] and their temporal dynamics to capture seasonal changes.

Satellite imagery is not the sole data source used for LC mapping. For instance, GFC was generated without directly relying on satellite data; instead, it utilized various publicly available land cover and land use datasets (e.g., WorldCover, GSW), as well as tree cover and tree height datasets, to produce a representation of forest presence or absence in 2020 at a 10-meter spatial resolution[39]. Some datasets integrate satellite imagery with auxiliary data to enhance classification accuracy. For example, GWL_FCS30D incorporates GlobeLand30 to refine non-wetland samples, thereby improving sample accuracy. Additionally, this dataset leverages the ASTER Global Digital Elevation Model (ASTER DEM) to capture elevation features, enabling the characterization of topographical variability associated with wetlands[30].

1.2. Preprocessing

Before being used for land cover mapping, remote sensing data are typically preprocessed to ensure consistency, accuracy, and usability. Given the diversity of data sources, preprocessing plays a vital role in mitigating issues such as geometric distortion, radiometric inconsistency, and cloud contamination. This section presents key preprocessing steps, including radiometric correction to normalize variations in sensor response, geometric correction to correct spatial misalignment, cloud masking to remove poor pixels, image fusion to integrate data from multiple sources, and resampling to standardize spatial resolution. Together, these steps enhance the reliability and comparability of multi-source datasets, facilitating more accurate land cover classification and analysis.

To mitigate atmospheric and topographic effects, radiometric calibration is commonly performed. The primary objective of atmospheric correction is to minimize the scattering and absorption effects caused by the atmosphere in optical multispectral images, thereby obtaining surface reflectance values. Various GHRLC datasets employ standardized correction algorithms to achieve this. For instance, GLC_FCS30D and GISD30 used official algorithms such as the Landsat Ecosystem Disturbance Adaptive Processing System (LEDAPS)[44] and the Land Surface Reflectance Code (LaSRC) [45] to correct Landsat imagery to surface reflectance. Similarly, FROM-GLC applies an enhanced version of the Fast Line-of-Sight Atmospheric Analysis of Spectral Hypercubes (FLAASH) algorithm[46] for atmospheric correction of Landsat TM and ETM+ Scenes.

However, the necessity of atmospheric correction depends on the processing level of the optical satellite imagery used. For example, MapBiomass relies on Landsat Tier 1 imagery, which has already been atmospherically corrected using LaSRC. Likewise, Sentinel-2 Level-2A (L2A) products, as used in GHRLCs such as ESRI LULC[17] and WorldCover[18,19], provide radiometrically calibrated surface reflectance (SR) processed using the Sen2Cor software package, eliminating the need for additional correction at the preprocessing stage.

In addition to atmospheric correction, relative radiometric normalization is sometimes applied to Landsat images to ensure consistency across different sensor generations. For

example, GLC_FCS30D used transformations[47] to normalize differences in wavelength responses between the Landsat Thematic Mapper (TM), Enhanced Thematic Mapper Plus (ETM+), and Operational Land Imager (OLI) sensors. This normalization enhances the comparability of datasets derived from different Landsat sensors, thereby improving the continuity and reliability of multi-temporal analyses.

Some GHRLCs also incorporate terrain correction during preprocessing to mitigate the influence of topography on surface reflectance. For example, FROM-GLC30 applies the TopoRadCor process[7] to perform topographic correction on Landsat imagery, ensuring more accurate surface reflectance values in areas with complex terrain.

For SAR-based land cover mapping, terrain correction is often necessary to account for distortions caused by topographic variations. For instance, WorldCover applies terrain correction to generate a Gamma0 backscatter time series[48], improving the consistency of Sentinel-1 GRD imagery. Similarly, GHS BU S1, following thermal noise removal, undergoes radiometric calibration to sigma nought (dB) using Sentinel-1 Level-1 GRD images. The dataset further applies terrain correction using the Shuttle Radar Topography Mission (SRTM) Digital Elevation Model (DEM) at a 1-arc-second resolution and the Advanced Spaceborne Thermal Emission and Reflection Radiometer (ASTER) Global Digital Elevation Model Version 2 (GDEM V2)[38]. These corrections help to reduce elevation-induced distortions, enhancing the accuracy and reliability of land cover classification, particularly in mountainous regions.

To further enhance data accuracy, it is crucial to remove low-quality pixels that may degrade classification performance. Different GHRLCs employ various strategies depending on the data sources they utilize. For instance, GWL_FCS30D[30], GISD30[11], and WSF apply the CFmask (C Function of Mask) algorithm to identify and mask poor-quality observations in Landsat imagery[34], effectively removing clouds, cloud shadows, and other contaminants. Similarly, WorldCover utilizes the Scene Classification Layer (SCL) from Sentinel-2 Level-2A products to filter out cloud-covered and noisy pixels[18,19], ensuring cleaner input data. Some datasets implement more advanced cloud-masking techniques. Dynamic World combines Sentinel-2's Cloud Probability (S2C) product with the Cloud Displacement Index (CDI) algorithm, integrating probability-based cloud detection with displacement effect analysis to generate high-precision cloud masks[20]. Other approaches aim to restore missing or corrupted data. GlobeLand30 employs the Neighborhood Similar Pixel Interpolator (NSPI) method[8], which reconstructs cloud-affected and missing pixels (such as Landsat ETM+'s SLC-off gaps) by interpolating similar pixels from neighboring temporal and spatial data.

When integrating multiple data sources, it is essential to ensure consistency in spatial resolution, coordinate systems, and temporal coverage across different datasets. For example, Dynamic World applies bilinear upsampling to 10-meter resolution for all used bands of Sentinel-2 Level-1C imagery[20], which ensures that data from different spectral bands are processed at a uniform spatial scale. Similarly, datasets derived from multi-resolution sources face challenges in harmonization. GFC, which integrates public datasets of varying spatial resolutions, does not explicitly specify its resampling methodology. However, it points out that discrepancies in spatial resolution among input datasets can lead to sharp boundaries between forested and non-forested areas, potentially resulting in underestimated forest edge detection[39].

These diverse preprocessing techniques are essential for enhancing the consistency, completeness, and reliability of input datasets used in land cover mappings, ultimately improving the accuracy and applicability of the resulting land cover products.

1.3. Automatic Classification

Automatic classification methods are a crucial step for the generation of reliable land cover maps by the analysis of pre-processed satellite images. From traditional rule-based and statistical techniques, to more automated and scalable machine learning and deep learning models, classification methods have undergone a major transformation, which




Figure 1. Evolution of HRLC mapping methods from 2013 to 2024

reflects technological progress and the shift to more sophisticated data-driven techniques. This section will analyze the main techniques and methods used in the studied HRLCs (as shown in Figure 1), explore the historical development of classification techniques and their impact on land cover mapping, as well as the present trends.

Traditional land cover mapping relied on expert knowledge to establish classification rules, utilizing manual interpretation and rule-based models. These methods, which define decision rules based on spectral features, typically require extensive domain expertise and are primarily used for binary classification. For instance, the FNF forest map is generated using backscatter thresholds specific to certain regions, achieving an overall accuracy exceeding 91% when validated against Google Earth Imagery (GEI)[40]. However, while multiple thresholds were applied, they were generally defined based on common forest types. As a result, certain types, such as oil palm and coconut plantations, were misclassified due to their differing spectral characteristics. The development of GSW also utilized an expert system classifier, which applied a series of predefined decision rules to distinguish between water and non-water surfaces[9]. This approach leveraged both the multi-spectral and multi-temporal attributes of the Landsat archive but relied on manually set thresholds. Despite their effectiveness in some specific cases, these rule-based methods are highly dependent on prior knowledge, making them susceptible to subjective bias. Furthermore, the predefined rules limit adaptability to complex landscapes or atypical surface conditions, reducing their flexibility and overall robustness in large-scale or diverse environments.

The widespread availability of freely accessible geospatial data, including remote sensing imagery, along with advancements in algorithms and computing infrastructure, has made machine learning-based LC mapping more popular than ever. Machine learning techniques enable the analysis of larger and more complex datasets, yielding more accurate LULC classification results at broader spatial scales [49]. Gong et al.(2013)[7] produced the first 30 m resolution GHRLC (FROM-GLC) using four classifiers—Maximum Likelihood Classification (MLC), J4.8, Random Forest (RF), and Support Vector Machine (SVM)—to assess the effectiveness of machine learning approaches in HRLC mapping. It demonstrated that machine learning methods outperformed traditional approaches, with SVM achieving the highest overall classification accuracy (64.9%), followed by RF (59.8%), J4.8 (57.9%), and MLC (53.9%). Many other studies confirmed the same conclusions. Among the HRLC datasets reviewed in this study, RF emerged as the most frequently utilized machine learning algorithm, followed by SVM, as summarized in Table 3.

Table 3. An overview of machine learning methods used for generating HRLC products

Classification Method	Used In
Random Forest	[7,10,11,14,30,31,33,35]
Support Vector Machine	[7,34,36]
Gradient Boosting Decision Tree (CatBoost)	[18,19]
Symbolic Machine Learning (SML)	[37,38]
Decision Tree	[7]

If properly trained, ML methods improve generalization capabilities and can properly model complex scenarios. In traditional machine learning, feature extraction and classification are separated processes. The choice of the features is done in the phase of system design, often relying on specific feature engineering and feature selection strategies. On the contrary, more recent deep learning approaches integrate feature extraction and classification in the learning process, eliminating the need for manual feature extraction design. Furthermore, deep learning can also handle highly complex big data more effectively [50,51]. The ESRI LULC dataset employs a U-Net deep learning architecture, achieving an overall accuracy of 85% across ten classes[17]. Google’s Dynamic World leverages a fully convolutional neural network (FCNN) to produce near-real-time land cover classifications, with a reported overall agreement of 73.8% between model outputs and expert-labeled data[20].

Despite its advantages, the application of deep learning to global HRLC mapping is still limited. One of the main limitations of these approaches is the requirements to have a very large number of labeled samples in the learning phase. Besides, recent advances in attention mechanism-driven deep models, particularly vision transformers (ViT), have sparked a growing interest in their adaptation for LC mapping ([52–54]). Given their promising performance in other domains, we look forward to broader adoption of transformer and vision-based AI models for global LC mapping in the future.

2. Legends

A fundamental prerequisite for land cover mapping is the definition of a categorization system for the land cover classes. Different HRLC datasets employ different classification schemes because of varying thematic requirement, regional priorities, and mapping objectives. Some land cover products adopt standardized classification systems directly. For example, FAO Land Cover Classification System (LCCS), a hierarchical framework that define land-cover class by a dynamic combination of classifiers, is utilized by WorldCover. Other products develop entirely customized classification schemes to meet specific mapping requirements, as seen in FROM-GLC30. Meanwhile, some datasets integrate multiple existing standards and/or related products to define their classification schemes. For instance, Dynamic World’s classification scheme was developed through a review of multiple global LULC maps (USGS Anderson classification system[55], ESA Land Use and Coverage Area frame Survey land cover modalities[56], MapBiomass[35], and GlobeLand30[8]) and designed to align closely with IPCC land use classes[57]. GLC_FCS30D inherits its classification scheme from the CCI_LC products, which, in turn, are based on the FAO LCCS and compatible with the GLC2000, GlobCover 2005 and 2009 products. Additionally, some datasets integrate regional classification systems to develop more localized classification schemes. For example, MapBiomass employs a hierarchical classification system that merges FAO LCCS with those of the IBGE LCCS, ensuring regional relevance. These differences require a reclassification step to ensure compatibility for comparative analyses. Similarly, GLanCE30 Level 1 classes are similar to the USGS LCMAP classification[58] and align with the IPCC’s top-level land categories for greenhouse gas inventory reporting.

2.1. Legend harmonization

To facilitate inter-comparability or integration, classification system harmonization is required. Crosswalking methods for LC typically assign harmonized LC (HLC) classes to pixels based on votes from source LC (SLC) labels. These methods establish class associations using either binary values (associated or not) (hard association) [20,59,60] or continuous semantic affinity scores (soft association) [61] to measure the thematic correspondence between SLC and HLC classes. While such methods follow predefined rules, they are generally performed manually, requiring domain expertise. This not only makes the process time-consuming but also introduces subjectivity and potential inconsistencies. Furthermore, different HRLC products often adopt different classification systems, resulting in non-corresponding class definitions. For example, the flooded vegetation class in Dynamic World[20] and ESRI LULC[17] includes rice paddies and other heavily irrigated/inundated agriculture, whereas WorldCover incorporates this type of land cover into the cropland class. Similarly, the definition of water varies across these products: WC explicitly specifies a persistency time threshold (more than 9 months) while allowing for certain exceptions, whereas Dynamic World and ESRI LULC lack such constraints[62]. Consequently, linking these categories may introduce uncertainty, leading to inconsistencies not only in cross-comparisons but also in integration. Therefore, standardizing the LC classification system to address differences in LC class definitions and to harmonize class definitions is essential to improve the consistency and comparability of large-scale LC maps.

Furthermore, when comparing different LC products, a relatively simple classification system is often employed to harmonize classes across datasets. This approach typically aggregates fine-grained classes, leading to the loss of specific land types (e.g., wetland subtypes, forest subclasses), which in turn affects the accuracy assessment of these LC products. Additionally, certain LC products demonstrate superior performance in specific categories, and simple class merging may obscure these strengths, introducing distortions in accuracy comparisons. A possible solution to address these challenges is to adopt a multi-level classification scheme, allowing for comparisons at varying levels of granularity to better capture differences and maintain classification integrity.

3. Validation

3.1. Sampling method

In addition to the factors mentioned so far, the reliability of land cover maps also heavily depends on the validation methods employed. In fact, validation methodology inherently involves two important steps: sampling and accuracy assessment. On the other hand, sampling refers to the design protocol for selecting data that serve as a reference (i.e., ground truth) [63] and are used to validate land cover products. On the other hand, accuracy metrics quantify the degree of correctness in classification [63]. In this section, we review recent literature on global land cover validation, examining trends in the use of both sampling and accuracy assessment techniques, as well as potential challenges in their application to global and multi-temporal land cover products. In Table 4, we have compiled the sampling methods and sample sizes used for validation in the reviewed studies focusing on global land cover mapping. Additionally, we have noted whether the authors adopted a multi-temporal validation approach and the challenges they addressed.

Table 4. Summary of validation sampling approaches and sample sizes from the reviewed studies.

Study	Validation Sampling Approach	Number of Validation Samples
Gong et al. (2013) [7]	Non-systematic training; systematic unaligned testing	38,664 test samples

Continued on next page

Table 4. (Continued) Summary of validation sampling approaches and sample sizes from the reviewed studies.

Study	Validation Sampling Approach	Number of Validation Samples
Shimada et al. (2014) [40]	Targeted selection from multi-resolution segmentation	4114 points (1456 forest, 2548 non-forest)
Yu et al. (2014) [32]	Manual sampling from Landsat imagery with MODIS time series	38,664 testing samples
Chen et al. (2015) [8]	Two-rank sampling (map sheet and feature sampling)	159,874 pixel samples
Almeida et al. (2016) [64]	Geographically random sampling	535 points
Pekel et al. (2016) [9]	Stratified random sampling using 1° x 1° grid cells	40,124 control points
Corbane et al. (2019) [65]	Stratified random sampling with manual block interpretation	300 sample blocks (150 urban, 150 non-urban)
Gong et al. (2019) [31]	Multi-seasonal sampling; Not specified	140,000 validation units
Marconcini et al. (2020) [34]	Stratified random sampling per 1° unit	500 settlement and 500 non-settlement per unit; 900,000 total cells
Li et al. (2020) [66]	Random sampling across cities with seasonal composites	2,000 points per city; Test set = 1/5 of training
Karra et al. (2021) [17]	Random stratified sampling of 5km x 5km image chips	409 gold standard tiles
Marconcini et al. (2021) [33]	Iterative sampling with crowd-sourcing validation	180,000 reference cells (WSF-Evolution); 700,000 for WSF2019
Potapov et al. (2021) [67]	Stratified random sampling with 100 samples per stratum	500 samples per region; 3,500 total for croplands
Zhang et al. (2021) [61]	Automated extraction using CCI_LC and refinement rules; stratified random sampling for validation	44,043 validation samples
Brown et al. (2022) [20]	Stratified random sampling by regions and biomes	409 tiles; 1,636 annotations
Friedl et al. (2022) [10]	Simple and stratified random sampling	North America: 1,630 reference points
Hansen et al. (2022) [68]	Stratified random sampling with area-weighted selection	950 sample points globally
Potapov et al. (2022) [69]	Stratified random sampling by thematic product	Forest: 5,000 pixels; Cropland: 3,500; Built-up: 400; Water: 600; Snow: 500

Continued on next page

Table 4. (Continued) Summary of validation sampling approaches and sample sizes from the reviewed studies.

Study	Validation Sampling Approach	Number of Validation Samples
Yu et al. (2022) [70]	Spectral clustering for training; random sampling for validation	36,000 validation samples
Zhang et al. (2022) [11]	Automated derivation from impervious surface products with refinement rules	23,322 validation samples
Zhang et al. (2023) [12]	Stratified random sampling for wetland mapping with multi-sourced training	25,709 validation samples
Zhang et al. (2024) [30]	Refinement of a global sample pool with multi-temporal consistency checks; stratified random sampling for validation	Preliminary sample size: 24,000; Final: 22,719 validation points
Zhang et al. (2024) [14]	Automated training using change detection masks; stratified random sampling with independent datasets for validation	84,526 global validation samples; additional regional datasets (LCMAP, LUCAS)

3.1.1. Simple sampling method

Simple sampling is a widely used method in which each population unit has an equal chance of being selected. Since there is no further distribution into classes, the final evaluation using the metric is relative to the specific product under assessment. In fact, the biggest disadvantage of this approach is that some dispersed or small population classes may end up being underrepresented. An example of this can be seen in the study by Almeida et al. [64], where random sampling was implemented on a geographical basis to validate their classification map. Instead of using multi-temporal or multi-source data for classification, the authors selected 535 points for validation across all classes from a single high-resolution image. While this method provided a validation baseline, certain limitations were evident, such as the potential for uneven representation of certain land cover classes and the reliance on single-date imagery.

Scholars, such as Foody [71], emphasize that simple random sampling can be considered suitable without compromising the reliability of the final product, but only when all land cover classes are sufficiently represented in the population sample. Moreover, it is suggested to take into account potential constraints related to the study area during the design process and to avoid random sampling when working with large areas [71]. Nevertheless, it is a highly versatile approach that can be easily adopted in combination with other methods, such as stratified or cluster sampling [72].

3.1.2. Stratified sampling method

Beyond simple random sampling, stratified sampling is another widely used technique. The goal of this approach is to group the samples into distinct strata, ensuring that each sample belongs to a single stratum [72]. Two main types of strata discrimination can be distinguished: one based on map class and the other on spatial location. The former allows for the increased representation of rare land cover types, while the latter enhances representation for specific, usually small areas or helps introducing a spatially balanced sample [72]. In either case, the implementation of this approach improves the statistical reliability of accuracy assessments by generating precise accuracy estimates for each class.

Among the various implementations of this method, a few studies stand out for integrating additional criteria. For instance, in the case of Dynamic World, Brown et al. [20] divided the world into three regions (Western Hemisphere, Eastern Hemisphere-1, and Eastern Hemisphere-2), further subdividing each region into 14 biomes and using an auxiliary land cover dataset for stratification.

Hansen et al. [68] also employed stratified random sampling based on 19 strata representing typical global land cover classes. Initially, they generated random points globally, weighted by the area of 1° , to ensure an equal probability of selection for each point. Each point was then assigned to the corresponding stratum based on its location, with the final selection including the first 50 points for each stratum.

Chen et al. [8] detailed a two-rank sampling strategy for GlobeLand30, involving both map sheet sampling and feature sampling. In the first rank, map sheets ($6^\circ \times 5^\circ$ grids) were selected from a global inventory of 847 sheets covering all continents. In the second rank, feature samples of each land cover type were selected using spatial stratification sampling within the chosen map sheets.

3.1.3. Systematic sampling method

Systematic sampling is another basic method for sample selection, where representative units are defined at regular intervals [72]. It is usually applied when the aim is to achieve spatial balance, ensuring that the area of interest has a well-distributed numerical coverage. Some advantages of this method include its ease of implementation and, in contrast to simple random sampling, its ability to improve population variability by reducing potential sample clustering. On the other hand, its implementation may lead to periodicity bias if the selected interval coincides with a pattern in the population. A more robust alternative to systematic sampling is the use of the stratified method [73].

In fact, from the reviewed studies focused on global land cover mapping (4), it is evident that systematic sampling is not a favoured methodology. The only notable implementation is found in Gong et al. [7], where the authors applied systematic unaligned sampling by first dividing the globe into approximately 7,000 equal-area hexagons. They then assigned different sample counts: 10 per hexagon for Europe and China, and 5 for the rest of the world. The final sample collection resulted in more than 35,000 valid samples.

3.1.4. Clustered sampling method

Clustered sampling is a methodology that involves dividing the population into small groups (clusters). Two distinct approaches are often adopted: one-stage cluster sampling, where sampling is conducted directly on the primary clustered units, and two-stage cluster sampling, where samples are selected within the primary clusters [63,72]. One of the key advantages of its implementation is cost-effectiveness, as once an interpretation is made for a pixel within a cluster, the effort required for an additional one in the same group is significantly lower [63].

An example of such sampling can be seen in the methodology applied by Marconcini et al. [34] for validating the World Settlement Footprint. In this approach, an initial clustering of tiles (each $1^\circ \times 1^\circ$ in size) was conducted, followed by the selection of 50 tiles which can be interpreted as clusters. Finally, individuals from both classes (settlement and non-settlement) were sampled within the selected tiles.

Moreover, clustering can be carried out not only spatially but also using additional criteria. To augment their training samples, Friedl et al. [10] applied unsupervised clustering based on spectral-temporal features using Landsat time-series imagery.

3.1.5. Sample size selection

The selection of an appropriate sample size is an integral and crucial step in the validation design of many spatial analyses, including global and regional land cover mapping. Several suggested designs can be noted in the literature. Among the empirical general rules we mention the proposition by Hay et al. [74], which recommends including

at least 50 samples per category for which accuracy is tested. However, later it was clarified that this rule [75] should be followed only when the area of interest is under 500,000 ha and less than 12 thematic classes are present [76].

In the literature, two statistically based criteria are favoured during the design process. A widely used approach is the formula proposed by Cochran [77], which ensures that the total estimated sample size is reliable within a certain confidence level and error margin. A more refined method, particularly focused on the sample size per stratum [77,78], uses the overall sample size while also considering the permissible error level and the proportion of the stratum covering the study area. This leads to weighted sample selection and better allocation in underrepresented classes, effectively addressing the issue of accuracy imbalance. Olofsson et al. [78] further proposed a simplified iterative sample size selection method by initially assigning a minimum of 50 samples for a rare stratum and monitoring the anticipated standard errors of accuracy. The process is iteratively adjusted until the desired precision levels for accuracy are achieved. This approach ensures efficient allocation while minimising variance without introducing bias into the estimators.

Among the reviewed literature on global land cover mapping, all scholars have reported the sample size used for validation (4). However, it is notable that not all studies have explicitly discussed the motivation behind the final sample size selection. Naturally, many applications are based on the requirement that the selected population should satisfy a certain error margin or class-specific accuracy (e.g., [8,12,40,61,64]).

Some studies have conducted experiments by adjusting their sample sizes to quantitatively analyse the effect on final accuracy. Gong et al. [7] modified their test sample size in a cluster and found that varying the number of samples did not lead to drastic changes in final accuracies.

On the other hand, few studies use a sample size that directly results from the application of additional design criteria. An example is the creation of the population used in validating the Dynamic World product [20], where the actual product is not based on a single static image classification but rather on a temporal basis using Sentinel-2 scenes. Here the validation set is a product of a more complex training/testing dataset definition, comprising spatial and thematic stratification, followed by expert and non-expert annotations. Similarly, Marconcini et al. [34] implemented a percentile-based criterion for tile selection based on the ratio between the number of settlements and their overall area.

3.2. Sample interpretation

Another important step in validation design, directly related to sample generation, is sample interpretation. In the land cover mapping domain, this refers to assigning a reference land cover class to each unit. From the reviewed works on global land cover mapping, several approaches can be highlighted, ranging from more traditional and well-established methods (e.g., photo interpretation) to more innovative automated ones (e.g., property-based clustering), each with its own strengths and weaknesses.

3.2.1. Manual interpretation

Manual interpretation typically relies on human annotators classifying samples according to land cover classes. In many cases, these interpretations are desktop-based, using high-resolution remotely sensed imagery, which generally allows for faster class identification. Some works [8] highlight the added benefits of class-specific, nature- and culture-based local knowledge. Nevertheless, the majority of studies rely on high-resolution photo interpretation, which can be further categorised into expert [7,10,11,14,20,36,64,65,67–69] and non-expert approaches [14,20].

The use of expert knowledge, particularly the involvement of multiple photointerpreters, is critical for improving the quality of training and test samples. Engaging trained professionals with expertise in land cover classification, remote sensing, and specific software tools typically leads to more consistent and accurate datasets. Additionally, the participation of multiple annotators results in more refined samples with higher confidence

in their class attribution. For example, Gong et al. [7]) involved more than 20 trained annotators at different stages of the interpretation process, based on their evaluated performance. Furthermore, their design process included a confidence classification to filter out samples where annotators were highly uncertain about the assigned class.

On the other hand, including non-experts in the interpretation process is generally beneficial for large-scale projects, where the number of samples to be processed is significantly high. This approach often prioritises "quantity over quality" and necessitates further quality assessment of the output samples. A similar methodology was applied in [20], where three experts and one non-expert were involved to benefit from cross-expert quality evaluation, further balancing accuracy with labelling efficiency. Zhang et al. [14] involved multi-level experts to independently interpret validation samples; however, the results from junior annotators required further cross-checking.

3.2.2. Automated interpretation

Methodologies for automatic sample interpretation (or creation) have emerged in recent years, with some examples leveraging data augmentation through unsupervised spectral clustering, which still requires photo interpretation [10,70]. These approaches have the potential to reduce the time required for sample generation. Other researchers have integrated auxiliary land cover products to generate training samples, using multiple land cover datasets and their points of agreement to create highly accurate training samples [59]. Similar auxiliary data have also been employed in global studies [11,12,65]. Zhang et al. [11] implemented a spectral-generalisation strategy for training set creation, although manual interpretation was still required for accuracy assessment. However, while such automated approaches are widely favoured for training set compilation, validation sets continue to rely primarily on manual interpretation.

3.2.3. Imagery data used for interpretation

As seen in the previous section, class annotation of reference samples using photo interpretation is a crucial step in all global studies. This process is directly linked to the dataset used and the requirements it must satisfy. One of the main data sources, optical imagery, presents certain limitations, such as cloud cover, resolution constraints, and spectral differences. To overcome these limitations, scholars often rely on multi-source and multi-resolution imagery. Upon review, it is notable that a few high- and medium-resolution datasets are frequently used for land cover class interpretation.

Table 5 summarises our findings regarding the most commonly used optical datasets for image interpretation. It is evident that the most favoured dataset source is the Landsat mission, primarily due to its provision of long-term medium-resolution data suitable for historical dynamic analyses. This is followed by Google Earth, which offers open access to very high-resolution images and, in many locations, provides relatively long time-series information. Notably, Sentinel-2 was used less frequently for sample interpretation compared to Landsat, despite its higher spatial and temporal resolution. This finding may be explained by the fact that the first Sentinel-2 satellite was launched in 2015 and the second in 2017, rendering the mission relatively "recent" with a more limited data archive compared to some of the works reviewed here. The last frequently implemented source is the MODIS mission, which, despite the moderate resolution, is highly suitable for extracting seasonal vegetation information and is favoured for its exceptionally high temporal resolution (1–2 days).

Table 5. Summary of data sources used for photo-interpretation.

Data Source	Resolution	Advantages	Used in
Landsat	30m (Multispectral), 15m (Panchromatic)	Long-term data record , time-series analysis, surface reflectance, identification of land cover dynamics	[8–10,14,38,61,65,67,69,70]
Google Earth VHR Imagery	0.15m to 1.5m (Varies depending on source)	Visual interpretation , validation of other satellite data, reference data source	[10,14,34,40,61,66,68–70]
Sentinel-2	10m, 20m, 60m (Varies by band)	High spatial, spectral, and temporal resolution , surface reflectance, land cover classification	[14,17,38]
MODIS	250m to 1km (Varies by product)	Time series vegetation indices (e.g., NDVI, EVI), extraction of seasonal vegetation information	[7,8,10,61,66,68,70]

It should be noted that not all of the reviewed papers were included in Table 5, even if they utilised optical imagery for reference. This is mainly because, in some cases, the specific data source was not explicitly mentioned. Conversely, some studies did not rely on optical imagery at all. Instead, certain works used domain-specific thematic auxiliary datasets, such as climate zones [66], or other land cover products, such as ESA CCI LC [14].

3.2.4. Crowdsourced data

Crowdsourced data has emerged as a valuable tool in land cover validation, enabling researchers to collect large-scale samples remotely from various geographic regions by leveraging contributions from both experts and non-experts. Furthermore, crowdsourced data supplements traditional validation methods with significantly greater availability of human-labelled data, utilising tools such as mobile apps (which provide high-resolution in-situ data) and online collaborative platforms (which allow for remote assessments).

It is evident that this approach could further support efforts to validate global land cover maps, as it has been implemented in a few of the reviewed works. For example, Friedl et al. [10] incorporated crowdsourced data, while Gong et al. [7] suggested using the GeoWiki global database of crowdsourced land cover sites [79]. This resource contains a vast amount of annotated cells (>150 million), yet further processing is required for case-specific applications. Similarly, after refinement, Zhang et al. [61] incorporated a class-specific dataset (global cropland reference data) obtained via crowdsourcing. Marconcini et al. [34] also harnessed the collective power of crowdsourcing through an unprecedented photo-interpretation campaign, annotating 900,000 samples using very high-resolution imagery. However, the reliability of crowdsourced data strongly depends on the definition of the land cover type.

3.3. Accuracy Metrics

The assessment of accuracy in land cover maps relies not only on the design choices made during the sampling process but also on the metrics used to quantify how well a classification model represents reality. The process of global land cover mapping has evolved significantly, and it is evident that scholars are shifting from simple agreement




Figure 2. Number of accuracy metrics used per study




Figure 3. Accuracy metrics used in reviewed studies

measures to more refined statistical indices that account for spatial and class-specific variations.

To better understand the frequency of usage of these metrics, we conducted a quantitative assessment based on the reviewed studies. Initially, we evaluated the number of metrics used per study (Figure 2). Notably, the majority of works rely on at least three or more validation metrics. In contrast, only one of the reviewed studies validated its results using a single indicator. To explain the interest in multiple validation metrics in the reviewed studies, we further explored the types of metrics implemented. Figure 3 presents the number of times each metric was used across different studies. Overall, the trends suggest a shift away from relying solely on aggregated indices, such as overall accuracy or kappa.

As global land cover classification processes become increasingly complex—both spatially and thematically—it has become evident that no single metric can fully capture classification performance. As a result, studies are implementing multiple complementary metrics to provide a more well-rounded evaluation while also offering better class-specific insights. In fact, the overall trends indicate a clear focus on the latter, with user's and producer's accuracies emerging as the most favoured, as they provide direct insights into both omission and commission errors.

Naturally, scholars also tend to implement generalised metrics, such as overall accuracy or kappa, which, while useful, can sometimes overlook important classification details.

A key example is the widespread use of overall accuracy, which, despite being a common measure, has limitations in handling class imbalances. Therefore, it is considered good practice to supplement it with class-specific evaluations. Similarly, kappa is generally regarded as a more robust measure complementary to class-specific metrics, as it accounts for the possibility of agreement occurring by chance and considers class imbalance. However, its limited usage is often attributed to its less intuitive interpretation and sensitivity to class sample size.

To address this issue, the variance of kappa (K_{var}) can be implemented to adjust for the influence of dominant classes, potentially making kappa more interpretable when class prevalence varies significantly. Despite being well-suited for unbalanced classes and better founded than Kappa for accuracy assessment, the F1-score remains rarely used, appearing in only two of the reviewed studies. Such limited implementation suggests that it has not yet become a standard metric in global land cover classification.

The practice of implementing multiple validation measures in combination is likely to persist, as the field of land cover classification (e.g., models and datasets) continues to evolve, reflecting broader trends in remote sensing and machine learning. Future studies are expected to continue evaluating classification performance at the class level rather than relying solely on singular global metrics.

4. Data distribution and cloud platforms

4.1. Data distribution

The accessibility and distribution of land cover mapping products play a critical role in their utilization across scientific research, environmental monitoring, and policy decision-making. The access points of all studied HRLCs in this paper can be found in Table A1.

Cloud-based platforms are now widely used for sharing and analyzing land cover data. They allow users access and process datasets without storing them locally. Google Earth Engine (GEE) is one of the most popular platforms. It hosts many datasets like GFC, FNF, and Dynamic World[20]. Amazon Web Services (AWS) Open Data also provides access to large-scale datasets, including GLanCE30 and GSW. These platforms help users to easily analyze data in the cloud.

Other than cloud platforms, some open data repositories give direct access to land cover datasets. Zenodo, for example, hosts land cover products like GLC_FCS30D and GISD30. It also provides DOI references so that researchers can cite and reuse the data. The China National Platform for Common Geospatial Information Services offers GlobeLand30 data to authorized users, making sure the distribution is controlled.

Many land cover datasets can be accessed through multiple ways. For instance, GSW data is available not only via GEE but also through the JRC portal, where users can manually select and download specific tiles or retrieve data via FTP services. ESA WorldCover, on the other hand, provides even more access options, including the WorldCover viewer, Terrascope, AWS S3 bucket, Zenodo, and GEE, accommodating various user preferences.

Land cover products are distributed in multiple formats to support different requirements. Raster-based formats like GeoTIFF are often used for direct spatial analysis. Some platforms also provide Web Map Services (WMS), which let users use the data in GIS platforms. Data availability is not the same for all products. Most datasets, such as ESA WorldCover, are freely available. Others, like GUF, need special permission to access.

The diversification of data distribution mechanisms allows users to select platforms and retrieval methods based on their needs, significantly enhancing data availability and usability across disciplines.

4.2. Trends in platform usage

GHRLC classification is a complex and resource-intensive task, requiring extensive data preprocessing, high performance computing, and high-quality training data to ensure both local reliability and global consistency [80].

Some LC products are generated using custom-developed platforms and computational environments. For instance, GUF dataset was produced using the Urban Footprint Processor, implemented at the German Remote Sensing Data Center (DFD) of the German Aerospace Center (DLR), generating a very high-resolution global human settlements layers at a spatial resolution of approximately 12 meters[36]. Similarly, GHS BU S1 was created using JRC Earth Observation Data and Processing Platform, designed for Earth observation (EO) data storage and processing[38].

Given the immense computational demands of large-scale LC mapping, many projects rely on supercomputers. For example, in WSF2015, the computation of Landsat-8 temporal statistics, training point extraction, and classification tasks was performed at the IT4Innovations Czech supercomputing center[34]. Likewise, all image classification tasks for FROM-GLC2010 were executed on the Tsinghua University supercomputer[7].

However, this on-premise computing relies on local computers and is limited by computing power, storage space, and data download costs. Therefore, more and more LC mapping tasks are performed on cloud-based computing platforms, which enable efficient processing without the need for local high-performance computing infrastructure. For example, ESRI LULC utilized Microsoft Planetary Computer and Microsoft Azure Batch to process over 20,000 Sentinel-2 tiles, which covers the entire Earth's land surface[17].

Among cloud-based platforms, Google Earth Engine (GEE) has become one of the most widely used due to its multi-petabyte data catalog, high-performance parallel computing capabilities, and extensive image-processing libraries that perform pixel-wise algebraic operations [81]. This, coupled with its ability to provide efficient and free access to a large number of remote sensing datasets, has led to its increasing use in HRLC classification. Take Dynamic World as an example, it uses cloud computing on GEE and Google Cloud AI Platform to generate near real-time predictions of LULC class probabilities for new and historical Sentinel-2 images[20]. GSW also deployed its expert system on GEE to achieve a dramatic increase in running speed from 1212 years to about 45 days[9].

Although cloud-based platforms have significantly improved efficiency, they still have several notable limitations. For example, GEE is constrained by compute limits, lack of processing algorithms and data, and limited flexibility of different models[82].

5. Discussing current trends and future directions

5.1. Multi-Source Data Fusion

Numerous studies[9–12,14,39] have highlighted that the accuracy of LC mapping is significantly influenced by both the availability and quality of Landsat data. Moreover, due to the limited temporal coverage of Sentinel-2 imagery, Dynamic World can only provide HRLC data starting from 2015. A promising solution to these limitations is data fusion, which involves integrating multiple data sources, including multi-sensor or multi-resolution datasets, to enhance the accuracy and reliability of LC classification. Jin and Mountrakis (2022)[83] shows that combining spaceborne optical data (Landsat-5/TM), SAR data (ALOS-1/PALSAR), and airborne full-waveform LiDAR (LVIS) significantly improves the discrimination of different land cover types. Beyond remote sensing data, auxiliary datasets have also proven valuable. For instance, Marconcini et al. (2021)[33] leveraged OpenStreetMap (OSM) data along with a novel dataset from Facebook that predicts missing roads in OSM to effectively mask out roads, thereby refining classification accuracy.

5.2. High Resolution and Real-Time Mapping

Despite significant advancements, real-time HRLC mapping remains a critical gap. Most of the HRLC products discussed in this study are annual maps, capturing LC conditions from past years, which limits their applicability for dynamic monitoring. A notable exception is Google's DW, the first GHRLC product capable of near-real-time updates. However, its performance varies across time and space, influenced by Sentinel-2 cloud cover quality and variability in land cover conditions. Meanwhile, the increasing availability of higher-resolution satellite imagery has paved the way for LC products with enhanced

spatial accuracy. For instance, Basheer et al. (2024)[84] achieved an overall classification accuracy of up to 94% for six land cover classes by using PlanetScope imagery (3-meter spatial resolution) and four supervised classifiers (SVM, ML, RF, and KNN). Thus, further improvements in both the spatial and temporal resolution of LC products remain a key priority for future research and development.

5.3. Computational Challenges

The increasing availability of high-resolution satellite imagery brings not only opportunities but also significant challenges for HRLC mapping. While these data enhance the potential for more precise land cover classification, they also place substantial demands on computational resources. Advanced algorithms, particularly deep learning models, on the other hand, have significantly improved classification accuracy but require robust computing power and efficient data processing pipelines. Although cloud-based platforms such as GEE have been widely adopted for HRLC mapping, they still face limitations, including constrained computational resources, a limited range of available algorithms, and incomplete data sources. Looking ahead, further advancements in cloud platforms are expected to provide more diverse algorithms and a more comprehensive collection of datasets, ultimately enhancing the efficiency and accuracy of HRLC mapping.

5.4. Standardized Datasets and Validation Protocols/Frameworks

Our review highlighted the diversity of sampling methods used in global land cover validation, with stratified random sampling emerging as one of the most widely preferred approaches for creating the reliable samples used for accuracy computations. Mainly, this is due to the fact the method efficiently addresses class imbalances and enhances statistical reliability. Moreover, systematic and clustered sampling methods offer certain advantages, such as spatial balance and cost-effectiveness, thus, their practical application to large-scale studies is notably. With regard to sample annotations, manual photo-interpretation (whether is expert and non-expert based) continues to be the dominant method, as it can offer highly-accurate reference dataset (especially when cross-referenced), naturally, on the cost of high manual and time-consuming workload. However, automated techniques, such as spectral clustering and the integration of auxiliary datasets, are emerging, offering a more scalable approach for augmented spatially distributed population samples. Similarly, accuracy assessment has evolved beyond simple overall accuracy metrics, with an increasing focus on class-specific measures, such as user's and producer's accuracies, which provide deeper insights into classification errors and model performance.

Despite these approaches emerging as a standard in land cover validation, the lack of standardised, high-quality reference datasets remains a significant challenge. Already Li et al. [85] has demonstrated that an all-seasons sample dataset brings a significant improvement of the classification outputs across the different temporal epochs. Similarly, Fritz et al. [79] highlighted the potential of crowdsourced land cover data as a scalable and cost-effective means of collecting validation samples. Establishing globally consistent, multi-temporal reference datasets will not only improve model validation methodologies but will also ensure greater reliability across different classification products and facilitate better intercomparison between land cover datasets.

6. Conclusions

This review provides a comprehensive analysis of the data sources, methodologies, and validation techniques utilized in over 20 binary or multi-class GHRLC products. It examines the usage of data sources and the preprocessing methods, from reliance on single-input datasets to the integration of satellite optical/SAR and other geospatial data. Additionally, it summarizes the progression of GHRLC production techniques, from early rule-based approaches to modern AI-driven methodologies, which leverage the computational power of cloud-based platforms.

A key focus of this review is the ongoing challenge of land cover legend harmonization, a crucial issue for ensuring consistency and comparability across datasets. Another fundamental aspect discussed is validation, which remains essential for assessing the accuracy and reliability of GHRLC products. The paper explores various validation methods, including statistical approaches and visual inspections, and highlights recent advancements in validation protocols, underscoring their role in maintaining data integrity and addressing emerging requirements, such as the development of standardized validation datasets.

Despite significant progress, challenges persist in areas such as data completeness, real-time processing, and reliable validation. Potential solutions include data fusion, enhancements of cloud-based platforms, and the establishment of standardized validation datasets and protocols. Moving forward, we anticipate the emergence of more globally consistent, real-time HRLC maps with improved accuracy and spatial resolution, which will support policymakers and stakeholders in making better decisions to meet global environmental challenges—from monitoring deforestation and urban expansion to supporting climate change mitigation strategies.

Author Contributions: Conceptualization, Q.X. and M.A.B.; methodology, Q.X. and M.A.B.; software, Q.X.; validation, Q.X. and V.Y.; formal analysis, Q.X., V.Y. and M.A.B.; investigation, Q.X. and M.A.B.; resources, Q.X.; data curation, Q.X.; writing—original draft preparation, Q.X. and V.Y.; writing—review and editing, M.A.B. and L.B.; visualization, Q.X. and V.Y.; supervision, M.A.B. and L.B.; project administration, M.A.B. and L.B.; funding acquisition, M.A.B. and L.B. All authors have read and agreed to the published version of the manuscript.

Funding: This research was funded by the European Space Agency (ESA) Climate Change Initiative Extension (CCI+) Phase 2 – New Essential Climate Variables (NEW ECVS) – High Resolution Land Cover project.

Conflicts of Interest: The authors declare no conflicts of interest.

Abbreviations

The following abbreviations are used in this manuscript:

LC	Land cover
HRLC	High-resolution land cover
GHRLC	Global High-resolution land cover
CAS	Chinese Academy of Sciences
ESA	European Space Agency
NASA	National Aeronautics and Space Administration
NGCC	National Geomatics Center of China
DLR	German Aerospace Center
JRC	Joint Research Centre

Appendix A

Appendix A.1

Table A1. Access points of HRLCs involved in this study.

Dataset name	Access point
GLC_FCS30D	https://zenodo.org/records/8239305
GWL_FCS30D	https://zenodo.org/records/10068479
GISD30	https://zenodo.org/records/5220816

Continued on next page

Table A1. (Continued) Access points of HRLCs involved in this study.

Dataset name	Access point
Dynamic World	GOOGLE_DYNAMICWORLD_V1
ESRI LULC	https://livingatlas.arcgis.com/landcover/
WorldCover	https://esa-worldcover.org/en/data-access
GLanCE v001	https://lpdaac.usgs.gov/products/glance30v001
GlobeLand30	https://cloudcenter.tianditu.gov.cn/landCover
FROM-GLC30	https://data-starcloud.pcl.ac.cn/
FROM-GLC10	https://data-starcloud.pcl.ac.cn/
World Settlement Footprint (WSF)	WSF2019
MapBiomias	https://brasil.mapbiomas.org/en/colecoes-mapbiomas/
GSW	https://global-surface-water.appspot.com/download
GUF	https://www.dlr.de/en/eoc/research-transfer/projects-missions/global-urban-footprint/guf-data-and-access
GHS-BUILT-S R2023A	GHS-BUILT-S R2023A
GHS BU S1	GHS BU S1 download link
GFC	https://forobs.jrc.ec.europa.eu/GFC
FNF	FNF download link
Tree canopy cover	hansen_global_forest_change

References

1. Sheykhoumou, M.; Kerle, N.; Kuffer, M.; Ghaffarian, S. Post-disaster recovery assessment with machine learning-derived land cover and land use information. *Remote sensing* **2019**, *11*, 1174.
2. Ghaffarian, S.; Rezaie Farhadabad, A.; Kerle, N. Post-disaster recovery monitoring with google earth engine. *Applied Sciences* **2020**, *10*, 4574.
3. Gaur, S.; Singh, R. A comprehensive review on land use/land cover (LULC) change modeling for urban development: current status and future prospects. *Sustainability* **2023**, *15*, 903.
4. Carter, S.; Herold, M. Specifications of land cover datasets for SDG indicator monitoring, 2019.
5. Roy, P.S.; Ramachandran, R.M.; Paul, O.; Thakur, P.K.; Ravan, S.; Behera, M.D.; Sarangi, C.; Kanawade, V.P. Anthropogenic land use and land cover changes—A review on its environmental consequences and climate change. *Journal of the Indian Society of Remote Sensing* **2022**, *50*, 1615–1640.
6. Szantoi, Z.; Geller, G.N.; Tsendbazar, N.E.; See, L.; Griffiths, P.; Fritz, S.; Gong, P.; Herold, M.; Mora, B.; Obregón, A. Addressing the need for improved land cover map products for policy support. *Environmental Science & Policy* **2020**, *112*, 28–35.
7. Gong, P.; Wang, J.; Yu, L.; Zhao, Y.; Zhao, Y.; Liang, L.; Niu, Z.; Huang, X.; Fu, H.; Liu, S.; et al. Finer resolution observation and monitoring of global land cover: first mapping results with Landsat TM and ETM+ data. *34*, 2607–2654. <https://doi.org/10.1080/01431161.2012.748992>.
8. Chen, J.; Chen, J.; Liao, A.; Cao, X.; Chen, L.; Chen, X.; He, C.; Han, G.; Peng, S.; Lu, M.; et al. Global land cover mapping at 30 m resolution: A POK-based operational approach. *103*, 7–27. <https://doi.org/10.1016/j.isprsjprs.2014.09.002>.
9. Pekel, J.F.; Cottam, A.; Gorelick, N.; Belward, A.S. High-resolution mapping of global surface water and its long-term changes. *540*, 418–422. <https://doi.org/10.1038/nature20584>.
10. Friedl, M.A.; Woodcock, C.E.; Olofsson, P.; Zhu, Z.; Loveland, T.; Stanimirova, R.; Arevalo, P.; Bullock, E.; Hu, K.T.; Zhang, Y.; et al. Medium Spatial Resolution Mapping of Global Land Cover and Land Cover Change Across Multiple Decades From Landsat. 3. Publisher: Frontiers, <https://doi.org/10.3389/frsen.2022.894571>.
11. Zhang, X.; Liu, L.; Zhao, T.; Gao, Y.; Chen, X.; Mi, J. GISD30: global 30 m impervious-surface dynamic dataset from 1985 to 2020 using time-series Landsat imagery on the Google Earth Engine platform. *14*, 1831–1856. Publisher: Copernicus GmbH TLDR: A novel and automatic method of combining the advantages of spectral-generalization and automatic-sample-extraction strategies

- was proposed, and an accurate and promising GSD30 dynamic dataset for 1985 to 2020 was produced using time-series Landsat imagery on the Google Earth Engine cloud computing platform., <https://doi.org/10.5194/essd-14-1831-2022>.
12. Zhang, X.; Liu, L.; Zhao, T.; Chen, X.; Lin, S.; Wang, J.; Mi, J.; Liu, W. GWL_FCS30: a global 30m wetland map with a fine classification system using multi-sourced and time-series remote sensing imagery in 2020. 15, 265–293. Publisher: Copernicus GmbH, <https://doi.org/10.5194/essd-15-265-2023>.
 13. Zhang, X.; Liu, L.; Chen, X.; Gao, Y.; Xie, S.; Mi, J. GLC_FCS30: global land-cover product with fine classification system at 30m using time-series Landsat imagery. 13, 2753–2776. Publisher: Copernicus GmbH, <https://doi.org/10.5194/essd-13-2753-2021>.
 14. Zhang, X.; Zhao, T.; Xu, H.; Liu, W.; Wang, J.; Chen, X.; Liu, L. GLC_FCS30D: the first global 30 m land-cover dynamics monitoring product with a fine classification system for the period from 1985 to 2022 generated using dense-time-series Landsat imagery and the continuous change-detection method. 16, 1353–1381. Publisher: Copernicus GmbH, <https://doi.org/10.5194/essd-16-1353-2024>.
 15. E. D. Chaves, M.; C. A. Picoli, M.; D. Sanches, I. Recent Applications of Landsat 8/OLI and Sentinel-2/MSI for Land Use and Land Cover Mapping: A Systematic Review. 12, 3062. <https://doi.org/10.3390/rs12183062>.
 16. Phiri, D.; Simwanda, M.; Salekin, S.; Nyirenda, V.R.; Murayama, Y.; Ranagalage, M. Sentinel-2 Data for Land Cover/Use Mapping: A Review. 12, 2291. <https://doi.org/10.3390/rs12142291>.
 17. Karra, K.; Kontgis, C.; Statman-Weil, Z.; Mazzariello, J.C.; Mathis, M.; Brumby, S.P. Global land use / land cover with Sentinel 2 and deep learning. In Proceedings of the 2021 IEEE International Geoscience and Remote Sensing Symposium IGARSS, pp. 4704–4707. ISSN: 2153-7003 TLDR: A deep learning segmentation model is developed and deployed on Sentinel-2 data to create a global LULC map at 10m resolution that achieves state-of-the-art accuracy and enables automated LULC mapping from time series observations., <https://doi.org/10.1109/IGARSS47720.2021.9553499>.
 18. Zanaga, D.; Van De Kerchove, R.; De Keersmaecker, W.; Souverijns, N.; Brockmann, C.; Quast, R.; Wevers, J.; Grosu, A.; Paccini, A.; Vergnaud, S.; et al. ESA WorldCover 10 m 2020 v100, 2021. <https://doi.org/10.5281/zenodo.5571936>.
 19. Zanaga, D.; Van De Kerchove, R.; Daems, D.; De Keersmaecker, W.; Brockmann, C.; Kirches, G.; Wevers, J.; Cartus, O.; Santoro, M.; Fritz, S.; et al. ESA WorldCover 10 m 2021 v200, 2022. <https://doi.org/10.5281/zenodo.7254221>.
 20. Brown, C.F.; Brumby, S.P.; Guzder-Williams, B.; Birch, T.; Hyde, S.B.; Mazzariello, J.; Czerwinski, W.; Pasquarella, V.J.; Haertel, R.; Ilyushchenko, S.; et al. Dynamic World, Near real-time global 10 m land use land cover mapping. 9, 251. <https://doi.org/10.1038/s41597-022-01307-4>.
 21. Pandey, P.C.; Koutsias, N.; Petropoulos, G.P.; Srivastava, P.K.; Ben Dor, E. Land use/land cover in view of earth observation: data sources, input dimensions, and classifiers—a review of the state of the art. 36, 957–988. Publisher: Taylor & Francis _eprint: <https://doi.org/10.1080/10106049.2019.1629647>, <https://doi.org/10.1080/10106049.2019.1629647>.
 22. Moharram, M.A.; Sundaram, D.M. Land use and land cover classification with hyperspectral data: A comprehensive review of methods, challenges and future directions. 536, 90–113. <https://doi.org/10.1016/j.neucom.2023.03.025>.
 23. Digra, M.; Dhir, R.; Sharma, N. Land use land cover classification of remote sensing images based on the deep learning approaches: a statistical analysis and review. 15, 1003. TLDR: A comprehensive review of distinct DL architectures and a custom framework to handle the challenging task of detecting changes in LULC are employed and a proposal for researchers to perform future potential using state-of-the-art methodologies is concluded., <https://doi.org/10.1007/s12517-022-10246-8>.
 24. Zhao, S.; Tu, K.; Ye, S.; Tang, H.; Hu, Y.; Xie, C. Land Use and Land Cover Classification Meets Deep Learning: A Review. 23, 8966. Number: 21 Publisher: Multidisciplinary Digital Publishing Institute TLDR: A systematic review of deep-learning-based LULC classification, mainly covering the main components of five typical deep learning networks, how they work, and their unique benefits., <https://doi.org/10.3390/s23218966>.
 25. Yele, V.P.; Sedamkar, R.; Alegavi, S. Systematic Analysis of Effective Segmentation and Classification for Land Use Land Cover in Hyperspectral Image using Deep Learning Methods: A Review of the State of the Art : Reviewing Deep Learning Techniques for Land Use and Cover in Hyperspectral Images. In Proceedings of the 2024 20th CSI International Symposium on Artificial Intelligence and Signal Processing (AISP), pp. 1–8. ISSN: 2640-5768 TLDR: This review paper delves into the intricate realm of segmenting and classifying Hyperspectral Images (HSI), complex visuals spanning numerous electromagnetic spectrum bands, and illuminates' gaps in HSI segmentation and classification., <https://doi.org/10.1109/AISP61396.2024.10475229>.
 26. Zhang, C.; Li, X. Land Use and Land Cover Mapping in the Era of Big Data. 11, 1692. Number: 10 Publisher: Multidisciplinary Digital Publishing Institute TLDR: This article summarizes the review studies and research progress in remote sensing, machine learning, deep learning, and geospatial big data for LULC mapping since 2015 and identified the opportunities, challenges, and future directions., <https://doi.org/10.3390/land11101692>.
 27. Wang, J.; Bretz, M.; Dewan, M.A.A.; Delavar, M.A. Machine learning in modelling land-use and land cover-change (LULCC): Current status, challenges and prospects. 822, 153559. TLDR: There is a need for multidisciplinary research beyond image processing and pattern recognition of machine learning in accelerating and advancing studies of LULCC modelling, and machine learning has strong potentials to incorporate new exploratory variables in modelling LUL CC through expanding remote sensing big data and advancing transient algorithms., <https://doi.org/10.1016/j.scitotenv.2022.153559>.
 28. Nedd, R.; Light, K.; Owens, M.; James, N.; Johnson, E.; Anandhi, A. A Synthesis of Land Use/Land Cover Studies: Definitions, Classification Systems, Meta-Studies, Challenges and Knowledge Gaps on a Global Landscape. 10, 994. Number: 9 Publisher: Multidisciplinary Digital Publishing Institute, <https://doi.org/10.3390/land10090994>.

29. Wang, Y.; Sun, Y.; Cao, X.; Wang, Y.; Zhang, W.; Cheng, X. A review of regional and Global scale Land Use/Land Cover (LULC) mapping products generated from satellite remote sensing. *206*, 311–334. <https://doi.org/10.1016/j.isprsjprs.2023.11.014>. 799
30. Zhang, X.; Liu, L.; Zhao, T.; Wang, J.; Liu, W.; Chen, X. Global annual wetland dataset at 30 m with a fine classification system from 2000 to 2022. *11*, 310. Publisher: Nature Publishing Group, <https://doi.org/10.1038/s41597-024-03143-0>. 800
31. Gong, P.; Liu, H.; Zhang, M.; Li, C.; Wang, J.; Huang, H.; Clinton, N.; Ji, L.; Li, W.; Bai, Y.; et al. Stable classification with limited sample: transferring a 30-m resolution sample set collected in 2015 to mapping 10-m resolution global land cover in 2017. *64*, 370–373. <https://doi.org/10.1016/j.scib.2019.03.002>. 801
32. Yu, L.; Wang, J.; Li, X.; Li, C.; Zhao, Y.; Gong, P. A multi-resolution global land cover dataset through multisource data aggregation. *57*, 2317–2329. <https://doi.org/10.1007/s11430-014-4919-z>. 802
33. Marconcini, M.; Metz-Marconcini, A.; Esch, T.; Gorelick, N. Understanding current trends in global urbanisation-the world settlement footprint suite. *9*, 33–38. 803
34. Marconcini, M.; Metz-Marconcini, A.; Üreyen, S.; Palacios-Lopez, D.; Hanke, W.; Bachofer, F.; Zeidler, J.; Esch, T.; Gorelick, N.; Kakarla, A.; et al. Outlining where humans live, the World Settlement Footprint 2015. *7*, 242. Publisher: Nature Publishing Group TLD: A new 10m resolution (0.32 arc sec) global map of human settlements on Earth for the year 2015, namely the World Settlement Footprint 2015, which considerably improves the detection of very small settlements in rural regions and better outlines scattered suburban areas., <https://doi.org/10.1038/s41597-020-00580-5>. 804
35. Souza, C.M.; Z. Shimbo, J.; Rosa, M.R.; Parente, L.L.; A. Alencar, A.; Rudorff, B.F.T.; Hasenack, H.; Matsumoto, M.; G. Ferreira, L.; Souza-Filho, P.W.M.; et al. Reconstructing Three Decades of Land Use and Land Cover Changes in Brazilian Biomes with Landsat Archive and Earth Engine. *12*, 2735. <https://doi.org/10.3390/rs12172735>. 805
36. Esch, T.; Marconcini, M.; Felbier, A.; Roth, A.; Heldens, W.; Huber, M.; Schwinger, M.; Taubenböck, H.; Müller, A.; Dech, S. Urban Footprint Processor—Fully Automated Processing Chain Generating Settlement Masks From Global Data of the TanDEM-X Mission. *10*, 1617–1621. <https://doi.org/10.1109/LGRS.2013.2272953>. 806
37. Pesaresi, M.; Schiavina, M.; Politis, P.; Freire, S.; Krasnodębska, K.; Uhl, J.H.; Carioli, A.; Corbane, C.; Dijkstra, L.; Florio, P.; et al. Advances on the Global Human Settlement Layer by joint assessment of Earth Observation and population survey data. *17*, 2390454. <https://doi.org/10.1080/17538947.2024.2390454>. 807
38. Corbane, C.; Pesaresi, M.; Politis, P.; Syrris, V.; Florczyk, A.J.; Soille, P.; Maffinini, L.; Burger, A.; Vasilev, V.; Rodriguez, D.; et al. Big earth data analytics on Sentinel-1 and Landsat imagery in support to global human settlements mapping. *1*, 118–144. Publisher: Taylor & Francis. 808
39. Joint Research Centre (European Commission).; Bourgoin, C.; Ameztoy, I.; Verhegghen, A.; Desclée, B.; Carboni, S.; Bastin, J.F.; Beuchle, R.; Brink, A.; Defourny, P.; et al. *Mapping global forest cover of the year 2020 to support the EU regulation on deforestation-free supply chains*; Publications Office of the European Union. 809
40. Shimada, M.; Itoh, T.; Motooka, T.; Watanabe, M.; Shiraishi, T.; Thapa, R.; Lucas, R. New global forest/non-forest maps from ALOS PALSAR data (2007–2010). *155*, 13–31. <https://doi.org/10.1016/j.rse.2014.04.014>. 810
41. Hansen, M.C.; Potapov, P.V.; Moore, R.; Hancher, M.; Turubanova, S.A.; Tyukavina, A.; Thau, D.; Stehman, S.V.; Goetz, S.J.; Loveland, T.R.; et al. High-Resolution Global Maps of 21st-Century Forest Cover Change. *342*, 850–853. <https://doi.org/10.1126/science.1244693>. 811
42. ESA. ESA - Sentinel-2. https://www.esa.int/Applications/Observing_the_Earth/Copernicus/Sentinel-2. 812
43. ESA. ESA - Sentinel-1. https://www.esa.int/Applications/Observing_the_Earth/Copernicus/Sentinel-1. 813
44. Masek, J.G.; Vermote, E.F.; Saleous, N.E.; Wolfe, R.; Hall, F.G.; Huemmrich, K.F.; Gao, F.; Kutler, J.; Lim, T.K. A Landsat surface reflectance dataset for North America, 1990–2000. *IEEE Geoscience and Remote sensing letters* **2006**, *3*, 68–72. 814
45. Vermote, E.; Justice, C.; Claverie, M.; Franch, B. Preliminary analysis of the performance of the Landsat 8/OLI land surface reflectance product. *Remote Sensing of Environment* **2016**, *185*, 46–56. Landsat 8 Science Results, <https://doi.org/https://doi.org/10.1016/j.rse.2016.04.008>. 815
46. Adler-Golden, S.M.; Matthew, M.W.; Bernstein, L.S.; Levine, R.Y.; Berk, A.; Richtsmeier, S.C.; Acharya, P.K.; Anderson, G.P.; Felde, J.W.; Gardner, J.; et al. Atmospheric correction for shortwave spectral imagery based on MODTRAN4. In *Proceedings of the Imaging Spectrometry V. SPIE*, 1999, Vol. 3753, pp. 61–69. 816
47. Roy, D.; Kovalskyy, V.; Zhang, H.; Vermote, E.; Yan, L.; Kumar, S.; Egorov, A. Characterization of Landsat-7 to Landsat-8 reflective wavelength and normalized difference vegetation index continuity. *Remote Sensing of Environment* **2016**, *185*, 57–70. Landsat 8 Science Results, <https://doi.org/https://doi.org/10.1016/j.rse.2015.12.024>. 817
48. Zanaga, D.; Van De Kerchove, R.; Daems, D.; De Keersmaecker, W.; Brockmann, C.; Kirches, G.; Wevers, J.; Cartus, O.; Santoro, M.; Fritz, S.; et al. WorldCover Product User Manual 2021 v200., 2022. 818
49. Zhang, C.; Li, X. Land Use and Land Cover Mapping in the Era of Big Data. *Land* **2022**, *11*. <https://doi.org/10.3390/land11101692>. 819
50. Kussul, N.; Shelestov, A.; Lavreniuk, M.; Butko, I.; Skakun, S. Deep learning approach for large scale land cover mapping based on remote sensing data fusion. In *Proceedings of the 2016 IEEE international geoscience and remote sensing symposium (IGARSS)*. IEEE, 2016, pp. 198–201. 820
51. Vali, A.; Comai, S.; Matteucci, M. Deep learning for land use and land cover classification based on hyperspectral and multispectral earth observation data: A review. *Remote Sensing* **2020**, *12*, 2495. 821
52. Yao, J.; Zhang, B.; Li, C.; Hong, D.; Chanussot, J. Extended Vision Transformer (ExViT) for Land Use and Land Cover Classification: A Multimodal Deep Learning Framework. *61*, 1–15. <https://doi.org/10.1109/TGRS.2023.3284671>. 822

53. Khan, M.; Hanan, A.; Kenzhebay, M.; Gazzea, M.; Arghandeh, R. Transformer-based land use and land cover classification with explainability using satellite imagery. *14*, 16744. <https://doi.org/10.1038/s41598-024-67186-4>. 858
54. Roy, S.K.; Sukul, A.; Jamali, A.; Haut, J.M.; Ghamisi, P. Cross Hyperspectral and LiDAR Attention Transformer: An Extended Self-Attention for Land Use and Land Cover Classification. *62*, 1–15. <https://doi.org/10.1109/TGRS.2024.3374324>. 859
55. Anderson, J.R.; Hardy, E.E.; Roach, J.T.; Witmer, R.E. A land use and land cover classification system for use with remote sensor data. Report 964. Edition: -, <https://doi.org/10.3133/pp964>. 860
56. Commission, E.; Centre, J.R.; Jones, A.; Fernández-Ugalde, O.; Scarpa, S. *LUCAS 2015 topsoil survey – Presentation of dataset and results*; Publications Office. <https://doi.org/doi/10.2760/616084>. 861
57. Penman, J.; Gytarsky, M.; Hiraishi, T.; Krug, T.; Kruger, D.; Pipatti, R.; Buendia, L.; Miwa, K.; Ngara, T.; Tanabe, K.; et al. *Good practice guidance for land use, land-use change and forestry*; Institute for Global Environmental Strategies. 862
58. Brown, J.F.; Tollerud, H.J.; Barber, C.P.; Zhou, Q.; Dwyer, J.L.; Vogelmann, J.E.; Loveland, T.R.; Woodcock, C.E.; Stehman, S.V.; Zhu, Z.; et al. Lessons learned implementing an operational continuous United States national land change monitoring capability: The Land Change Monitoring, Assessment, and Projection (LCMAP) approach. *238*, 111356. <https://doi.org/https://doi.org/10.1016/j.rse.2019.111356>. 863
59. Bratic, G.; Yordanov, V.; Brovelli, M.A. High-resolution land cover classification: cost-effective approach for extraction of reliable training data from existing land cover datasets. *International Journal of Digital Earth* **2023**, *16*, 3618–3636. 864
60. Duarte, D.; Fonte, C.; Costa, H.; Caetano, M. Thematic Comparison between ESA WorldCover 2020 Land Cover Product and a National Land Use Land Cover Map. *Land* **2023**, *12*. 865
61. Li, Z.; White, J.C.; Wulder, M.A.; Hermosilla, T.; Davidson, A.M.; Comber, A.J. Land cover harmonization using Latent Dirichlet Allocation. *International Journal of Geographical Information Science* **2021**, *35*, 348–374. 866
62. Venter, Z.S.; Barton, D.N.; Chakraborty, T.; Simensen, T.; Singh, G. Global 10 m Land Use Land Cover Datasets: A Comparison of Dynamic World, World Cover and Esri Land Cover. *14*, 4101. Number: 16 Publisher: Multidisciplinary Digital Publishing Institute, <https://doi.org/10.3390/rs14164101>. 867
63. Strahler, A.H.; Boschetti, L.; Foody, G.M.; Friedl, M.A.; Hansen, M.C.; Herold, M.; Mayaux, P.; Morisette, J.T.; Stehman, S.V.; Woodcock, C.E. Global land cover validation: Recommendations for evaluation and accuracy assessment of global land cover maps. *51*, 1–60. 868
64. Almeida, C.A.d.; Coutinho, A.C.; Esquerdo, J.C.D.M.; Adami, M.; Venturieri, A.; Diniz, C.G.; Dessay, N.; Durieux, L.; Gomes, A.R. High spatial resolution land use and land cover mapping of the Brazilian Legal Amazon in 2008 using Landsat-5/TM and MODIS data. *46*, 291–302. Publisher: Instituto Nacional de Pesquisas da Amazônia, <https://doi.org/10.1590/1809-4392201505504>. 869
65. Corbane, C.; Pesaresi, M.; Kemper, T.; Politis, P.; Florczyk, A.J.; Syrris, V.; Melchiorri, M.; Sabo, F.; Soille, P. Automated global delineation of human settlements from 40 years of Landsat satellite data archives. *3*, 140–169. <https://doi.org/10.1080/20964471.2019.1625528>. 870
66. Li, Q.; Qiu, C.; Ma, L.; Schmitt, M.; Zhu, X.X. Mapping the Land Cover of Africa at 10 m Resolution from Multi-Source Remote Sensing Data with Google Earth Engine. *12*, 602. Number: 4 Publisher: Multidisciplinary Digital Publishing Institute TLDR: After experimental evaluation of different land cover classes across different cities, it is concluded that continental land cover mapping results can be considerably improved when training samples of natural land cover Classes are collected and combined from areas covering each Köppen climate zone., <https://doi.org/10.3390/rs12040602>. 871
67. Potapov, P.; Turubanova, S.; Hansen, M.C.; Tyukavina, A.; Zalles, V.; Khan, A.; Song, X.P.; Pickens, A.; Shen, Q.; Cortez, J. Global maps of cropland extent and change show accelerated cropland expansion in the twenty-first century. *3*, 19–28. Publisher: Nature Publishing Group, <https://doi.org/10.1038/s43016-021-00429-z>. 872
68. Hansen, M.C.; Potapov, P.V.; Pickens, A.H.; Tyukavina, A.; Hernandez-Serna, A.; Zalles, V.; Turubanova, S.; Kommareddy, I.; Stehman, S.V.; Song, X.P.; et al. Global land use extent and dispersion within natural land cover using Landsat data. *17*, 034050. Publisher: IOP Publishing, <https://doi.org/10.1088/1748-9326/ac46ec>. 873
69. Potapov, P.; Hansen, M.C.; Pickens, A.; Hernandez-Serna, A.; Tyukavina, A.; Turubanova, S.; Zalles, V.; Li, X.; Khan, A.; Stolle, F.; et al. The Global 2000–2020 Land Cover and Land Use Change Dataset Derived From the Landsat Archive: First Results. *3*. Publisher: Frontiers, <https://doi.org/10.3389/frsen.2022.856903>. 874
70. Yu, L.; Du, Z.; Dong, R.; Zheng, J.; Tu, Y.; Chen, X.; Hao, P.; Zhong, B.; Peng, D.; Zhao, J.; et al. FROM-GLC Plus: toward near real-time and multi-resolution land cover mapping. *59*, 1026–1047. Publisher: Taylor & Francis _eprint: <https://doi.org/10.1080/15481603.2022.2096184>, <https://doi.org/10.1080/15481603.2022.2096184>. 875
71. Foody, G.M. Status of land cover classification accuracy assessment. *80*, 185–201. [https://doi.org/10.1016/S0034-4257\(01\)00295-4](https://doi.org/10.1016/S0034-4257(01)00295-4). 876
72. Stehman, S.V. Sampling designs for accuracy assessment of land cover. *30*, 5243–5272. <https://doi.org/10.1080/01431160903131000>. 877
73. Stehman, S.V.; Foody, G.M. Key issues in rigorous accuracy assessment of land cover products. *231*, 111199. <https://doi.org/10.1016/j.rse.2019.05.018>. 878
74. Hay, A.M. Sampling Designs to Test Land-Use Map Accuracy. 912
75. Congalton, R.; Gu, J.; Yadav, K.; Thenkabail, P.; Ozdogan, M. Global Land Cover Mapping: A Review and Uncertainty Analysis. *6*, 12070–12093. <https://doi.org/10.3390/rs61212070>. 913

76. Castillo-Santiago, M.; Mondragón-Vázquez, E.; Domínguez-Vera, R. Sample Data for Thematic Accuracy Assessment in QGIS. In *Land Use Cover Datasets and Validation Tools: Validation Practices with QGIS*; García-Álvarez, D.; Camacho Olmedo, M.T.; Paegelow, M.; Mas, J.F., Eds.; Springer International Publishing; pp. 85–96. https://doi.org/10.1007/978-3-030-90998-7_6. 915
77. Cochran, W.G. Sampling Techniques. p. 10. 916
78. Olofsson, P.; Foody, G.M.; Herold, M.; Stehman, S.V.; Woodcock, C.E.; Wulder, M.A. Good practices for estimating area and assessing accuracy of land change. *148*, 42–57. <https://doi.org/10.1016/j.rse.2014.02.015>. 917
79. Fritz, S.; See, L.; Perger, C.; McCallum, I.; Schill, C.; Schepaschenko, D.; Duerauer, M.; Karner, M.; Dresel, C.; Laso-Bayas, J.C.; et al. A global dataset of crowdsourced land cover and land use reference data. *4*, 170075. Publisher: Nature Publishing Group, <https://doi.org/10.1038/sdata.2017.75>. 918
80. Zhang, H.K.; Roy, D.P. Using the 500m MODIS land cover product to derive a consistent continental scale 30m Landsat land cover classification. *Remote Sensing of Environment* **2017**, *197*, 15–34. <https://doi.org/10.1016/j.rse.2017.05.024>. 919
81. Gorelick, N.; Hancher, M.; Dixon, M.; Ilyushchenko, S.; Thau, D.; Moore, R. Google Earth Engine: Planetary-scale geospatial analysis for everyone. *Remote Sensing of Environment* **2017**, *202*, 18–27. Big Remotely Sensed Data: tools, applications and experiences, <https://doi.org/10.1016/j.rse.2017.06.031>. 920
82. Yang, L.; Driscoll, J.; Sarigai, S.; Wu, Q.; Chen, H.; Lippitt, C.D. Google Earth Engine and Artificial Intelligence (AI): A Comprehensive Review. *Remote Sensing* **2022**, *14*. <https://doi.org/10.3390/rs14143253>. 921
83. Jin, H.; Mountrakis, G. Fusion of optical, radar and waveform LiDAR observations for land cover classification. *187*, 171–190. <https://doi.org/10.1016/j.isprsjprs.2022.03.010>. 922
84. Basheer, S.; Wang, X.; Nawaz, R.A.; Pang, T.; Adekanmbi, T.; Mahmood, M.Q. A comparative analysis of PlanetScope 4-band and 8-band imageries for land use land cover classification. *Geomatica* **2024**, *76*, 100023. <https://doi.org/10.1016/j.geomat.2024.100023>. 923
85. Li, C.; Gong, P.; Wang, J.; Zhu, Z.; Biging, G.S.; Yuan, C.; Hu, T.; Zhang, H.; Wang, Q.; Li, X.; et al. The first all-season sample set for mapping global land cover with Landsat-8 data. *62*, 508–515. <https://doi.org/10.1016/j.scib.2017.03.011>. 924

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content. 925
926
927
928
929
930
931
932
933
934
935
936
937